

# PRODUCT INFORMATION SHEET

Actual status: 15.02.18



## REMOTE DISPLAY- AND CONTROL PANEL MASTER PLUS XS-HOUSING

ABFplus Master XS GB

Part-No.: 32681



Microprocessor controlled modular master remote display control panel for the control of a network of fire control panels of the series detect 3004plus

- LC-Display 160 x 80 Pixel, backlit
- Integrated module for thIntegrated display and control panel according to DIN EN 54-2 A1 2006e connection to a network of fire control panels of the series detect 3004plus
- Up to 20 fire control panels respectively 30 components in one network
- Integrated RS-232 interface for the DPT programming software and the connection of printers and other peripheral equipment
- Connections for a fire brigade interface for controlling the panels outputs, key deposit and transmission units
- Option for full redundancy by redundant CPU
- Event log memory of up to 1.000 messages
- In accordance to EN 61000-6-3 class B for emissions, so suitable for the use in sensitive areas

### Technical Data

Supply Voltage	24 V DC
Quiescent Current	110 mA
Alarm Current	200 mA
Input	3 inputs for collective events
Display	LC-Display 160 x 80 pixel; backlit; 20 LED for status
Interfaces	RS-232; integrated Bitbus-Interface
Protection class	IP 30
Ambient temperature	-5°C to +40°C
Humidity	5% - 95% (not condensing)
Dimensions (H x B x T)	310 mm x 420 mm x 83 mm
Weight	6,0 kg
Material	Sheet metal
Colour	Light grey RAL 7035
Standards	54-2