



## ► GFE-MCPC

### Conventional Manual Call Point

The GFE-MCPC is a Conventional Manual Call Point, designed and manufactured to comply with **EN54-11**, compatible with all **GFE Conventional Control panels**. A bi-colour LED flashes Green when the unit is connected to a control panel and is illuminated Red when in Alarm.

The unit is supplied complete with a **hinged flap** which protects the trigger element from accidental activation and reduces malicious activations as **two actions** are required in order to activate the device. This unit can be both surface and flush mounted and it can be easily reset using the supplied key after activation.

| TECHNICAL SPECIFICATIONS               | GFE-MCPC   |
|--|--|
| SUPPLY VOLTAGE                         | 16-30 V DC                                       |
| CURRENT - QUIESCENT                    | 200 uA   |
| CURRENT - DEVICE IN ALARM              | 50 mA @ 24 V DC - Alarm Resistance 470 Ohms Max. |
| CABLE SIZE                             | 0.5-2.5 mm <sup>2</sup>                          |
| COLOUR / CASE MATERIAL / IP PROTECTION | Red / ABS Flame Retardant 94 V0 / IP24           |
| OPERATING TEMPERATURE                  | -10°C to 50°C                                    |
| MAX. HUMIDITY                          | 95% RH Non-Condensing                            |
| DIMENSIONS                             | 92 (W) x 92 (H) x 54 (D) mm                      |
| WEIGHT                                 | 152 g  |
| ORDER CODE                             | DESCRIPTION                                      |
| GFE-MCPC                               | Conventional Manual Call Point                   |